

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

SECTION 1. IDENTIFICATION

Product name : PB BLACK
SDS-Identcode : 513G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Telefax : 214-631-3047
Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887
(24-hours/7 days)
E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use


Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
pheres.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Carcinogenicity : Category 2
Reproductive toxicity : Category 1A
Effects on or via lactation
Specific target organ : Category 1 (Kidney, Central nervous system, Blood)
systemic toxicity - repeated
exposure

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H351 Suspected of causing cancer.
H360FD May damage fertility. May damage the unborn child.
H362 May cause harm to breast-fed children.
H372 Causes damage to organs (Kidney, Central nervous
system, Blood) through prolonged or repeated exposure.

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P263 Avoid contact during pregnancy/ while nursing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lead	7439-92-1	>= 30 - < 50
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
Talc	14807-96-6	>= 10 - < 20
Graphite	7782-42-5	>= 5 - < 10
Dolomite	16389-88-1	>= 1 - < 5
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 5
Quartz	14808-60-7	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

In case of eye contact : Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
: Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Suspected of causing cancer.
May damage fertility. May damage the unborn child.
May cause harm to breast-fed children.
Causes damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Lead compounds
Carbon oxides
Metal oxides
Silicon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for : Sweep up or vacuum up spillage and collect in suitable

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

containment and cleaning up container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lead	7439-92-1	TWA	0.05 mg/m ³ (Lead)	NIOSH REL
		TWA	0.05 mg/m ³ (Lead)	ACGIH
		PEL	0.05 mg/m ³ (Lead)	OSHA CARC
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
 Date of first issue: 05/13/2015

		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m ³	NIOSH REL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Dolomite	16389-88-1	TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
12-Hydroxy lithium stearate	7620-77-1	TWA (Inhalable fraction)	10 mg/m ³	ACGIH
		TWA (Respirable fraction)	3 mg/m ³	ACGIH
Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Lead	7439-92-1	Lead (Lead)	In blood	Not critical	200 µg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
- Hand protection
- Material : Chemical-resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
See 29 CFR 1910.1025 for additional requirements relating to lead exposure.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Viscous semi-solid
Color : black
Odor : Petroleum
Odor Threshold : No data available
- pH : Not applicable (not an aqueous solution)
- Melting point/freezing point : No data available

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

Initial boiling point and boiling range : No data available
Flash point : ≥ 392 °F / ≥ 200 °C
Method: ASTM D 92, Cleveland open cup
Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 2.2

Density : No data available

Solubility(ies)
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Can react with strong oxidizing agents.

PB BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
12.2	10/11/2018	117768-00017	Date of first issue: 05/13/2015

Conditions to avoid : None known.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Lead:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h

PB BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
12.2	10/11/2018	117768-00017	Date of first issue: 05/13/2015

Test atmosphere: dust/mist
 Method: OECD Test Guideline 403

Dolomite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 420
 Assessment: The substance or mixture has no acute oral toxicity
 Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity
 Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Assessment: The substance or mixture has no acute oral toxicity

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**Lead:**

Species : Rabbit
 Method : OECD Test Guideline 404
 Result : No skin irritation
 Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
 Result : No skin irritation
 Remarks : Based on data from similar materials

Talc:

Species : Rabbit
 Result : No skin irritation

PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

Graphite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Dolomite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Lead:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Talc:

Species : Rabbit
Result : No eye irritation

Graphite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Dolomite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

Species : Rabbit

PB BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
12.2	10/11/2018	117768-00017	Date of first issue: 05/13/2015

Result : No eye irritation
Remarks : Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Lead:**

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Talc:

Routes of exposure : Skin contact
Species : Humans
Result : negative

Graphite:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Dolomite:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse

PB BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
12.2	10/11/2018	117768-00017	Date of first issue: 05/13/2015

Method : OECD Test Guideline 429
 Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Lead:**

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells
 Result: negative
 Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Species: Rat
 Application Route: Ingestion
 Result: positive
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Species: Mouse
 Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
 Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
 Species: Rat
 Application Route: Ingestion
 Result: negative

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative

PB BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
12.2	10/11/2018	117768-00017	Date of first issue: 05/13/2015

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative

Dolomite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative
 Remarks: Based on data from similar materials

Carcinogenicity

Suspected of causing cancer.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components:**Lead:**

Species : Rat
 Application Route : Ingestion
 Exposure time : 2 Years
 Result : positive
 Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Mouse
 Application Route : Skin contact
 Exposure time : 78 weeks
 Method : OECD Test Guideline 451
 Result : negative

Talc:

Species : Mouse
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 2 Years
 Result : negative

Quartz:

Species : Humans
 Application Route : inhalation (dust/mist/fume)
 Result : positive
 Remarks : IARC: (International Agency for Research on Cancer)
 These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

PB BLACK

Version 12.2	Revision Date: 10/11/2018	SDS Number: 117768-00017	Date of last issue: 10/01/2018 Date of first issue: 05/13/2015
-----------------	------------------------------	-----------------------------	---

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

IARC	Group 1: Carcinogenic to humans Quartz (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans Lead	7439-92-1
OSHA	OSHA specifically regulated carcinogen Lead (Lead and inorganic lead compounds)	7439-92-1
NTP	Reasonably anticipated to be a human carcinogen Lead	7439-92-1
	Known to be human carcinogen Quartz (Silica, Crystalline (Respirable Size))	14808-60-7

Reproductive toxicity

May damage fertility. May damage the unborn child.
May cause harm to breast-fed children.

Components:**Lead:**

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Mouse Application Route: Ingestion Result: positive Remarks: Based on data from similar materials
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: positive Remarks: Based on data from similar materials
Reproductive toxicity - Assessment	: Positive evidence of adverse effects on sexual function and fertility from human epidemiological studies., Positive evidence of adverse effects on development from human epidemiological studies., Studies indicating a hazard to babies during the lactation period

Talc:

Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative
------------------------------	---

Graphite:

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the
----------------------	---

PB BLACK

Version 12.2	Revision Date: 10/11/2018	SDS Number: 117768-00017	Date of last issue: 10/01/2018 Date of first issue: 05/13/2015
-----------------	------------------------------	-----------------------------	---

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative

Dolomite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

Components:**Lead:**

Target Organs : Kidney, Central nervous system, Blood
 Assessment : Causes damage to organs through prolonged or repeated exposure.

12-Hydroxy lithium stearate:

Routes of exposure : Ingestion
 Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Quartz:

Routes of exposure : inhalation (dust/mist/fume)
 Target Organs : Lungs
 Assessment : Shown to produce significant health effects in animals at con-

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

centrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Lead:

Species : Rat
NOAEL : 0.0015 mg/kg
LOAEL : 0.005 mg/kg
Application Route : Ingestion
Exposure time : 6 - 12 Months
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rat
NOAEL : > 0.98 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Remarks : Based on data from similar materials

Dolomite:

Species : Mouse
NOAEL : 1,300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

Species : Rat
NOAEL : > 88 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Quartz:

Species : Humans
LOAEL : 0.053 mg/m³
Application Route : inhalation (dust/mist/fume)
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Lead:

PB BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
12.2	10/11/2018	117768-00017	Date of first issue: 05/13/2015

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 0.029 mg/l
Exposure time: 48 h
- Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.025 mg/l
Exposure time: 72 h
- EC10 (Pseudokirchneriella subcapitata (green algae)): 6.1 µg/l
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : EC10 (Pimephales promelas (fathead minnow)): 20 µg/l
Exposure time: 30 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Ceriodaphnia dubia (water flea)): 1.7 µg/l
Exposure time: 7 d

Distillates (petroleum), hydrotreated heavy naphthenic:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials
- Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Talc:

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
Exposure time: 24 h

Graphite:

- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Dolomite:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials
- Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
 Date of first issue: 05/13/2015

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Lead	7439-92-1	10	20

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Carcinogenicity
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Lead 7439-92-1 >= 30 - < 50 %

US State Regulations

Pennsylvania Right To Know

Lead	7439-92-1
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Talc	14807-96-6
Graphite	7782-42-5
Dolomite	16389-88-1
Quartz	14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including Lead, Quartz, which is/are known to the State of California to cause cancer, and Lead, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Lead	7439-92-1
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Talc	14807-96-6
Graphite	7782-42-5

California Permissible Exposure Limits for Chemical Contaminants

Lead	7439-92-1
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Talc	14807-96-6
Graphite	7782-42-5
Quartz	14808-60-7

California Regulated Carcinogens

Lead	7439-92-1
------	-----------

SAFETY DATA SHEET



PB BLACK

Version 12.2 Revision Date: 10/11/2018 SDS Number: 117768-00017 Date of last issue: 10/01/2018
Date of first issue: 05/13/2015

Quartz

14808-60-7


The ingredients of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- AICS : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	4
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- OSHA CARC / PEL : Permissible exposure limit (PEL)
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the

SAFETY DATA SHEET



PB BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
12.2	10/11/2018	117768-00017	Date of first issue: 05/13/2015

German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/11/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8