

BESTOLIFE® GGT



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color:	Black
Penetration: (ASTM D217)	310-330
NLGI Grade:	1
Weight/Gallon:	10.2 pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point:	≥392°F (≥200°C)
Brushable To:	10°F (-12°C)
Service Rating:	500°F (260°C)
Friction Factor:	1.0*
Shelf Life: (Unopened container)	4 years
Contains:	Synthetic graphite and other nonmetallic additives

*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

DESCRIPTION

BESTOLIFE® GGT is a non metallic compound formulated for light duty casing and tubing applications and pump columns.

APPLICATIONS

Graphite-based compound.

TECHNICAL DATA

GGT contains a high percentage of graphite and other inert solids that provide thread protection and sealing over a wide range of conditions and temperatures. The high quality base grease provides both corrosion protection and water resistance. GGT's excellent sealing properties, thermal stability and resistance to corrosion and water washout make it an ideal thread sealant and lubricant for any threaded connection where contact bearing stresses are not extreme. GGT will adhere to wet surfaces, will apply readily over a wide range of temperatures and will not harden with exposure or age. Contains no heavy metals such as lead, zinc or copper.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
652050	5 gallon	50 pounds plastic

Note: All package sizes are not listed. Call your sales representative for a complete listing.

