



1st Zinc® Primer Coat, 12.5 Wt OZ
 No. FZ-100 | Item# 1008303 | Case# 1008224

Product Description	95% pure zinc metal in traditional gray color. Meets or exceeds requirements of ASTM-A780, DOD-P-21035A, Mil-P-26915, Mil-P-46105.
Color	Gray
Applications	For parts and assemblies to be top-coated.
Unit Package Description	16 Ounce Aerosol
Brand	Weld-Aid
Generic Description 1	Corrosion Inhibitor
Net Fill	12.5 Wt Oz
UPC Code	731592810011
Unit Dimensions	9.25H x 2.75W x 2.75D in
Units Per Case	12
Case Dimensions	8.75H x 8.25W x 11.00D in
Cases Per Pallet	64
Case Weight	14.40 lbs
I 2 of 5 Code	30731592810012
Appearance	Gray Liquid
Flash point (F)	-4°F
Flash point (C)	-20°C
Flammability Class - CPSC	Flammable Aerosol
Plastic Safe	Not Determined
Evaporation Rate	Moderate
pH	Not Applicable
Dry Time - Fully Dry	24 Hours
Dry Time - Tack Free	15 Minutes
Recoat	15 Minutes
Coverage	Not Determined
Dielectric Strength	Not Determined

Last revised: 1/8/2020
 Page 1 of 2



Working Temp (F)	Not Determined
Working Temp (C)	Not Determined
Propellant	Butane,Propane
Aerosol Flammability Level	II
Military Specification Number	Mil-P-26915,Mil-P-46105,DOD-P-210352A
VOC % (Consumer Product def)	60.4
VOC g/L (Consumer Product def)	592
VOC lbs/gal (Consumer Prod def)	4.93
VOC Category	Metallic Coating
MIR Limit (EPA)	1.9
MIR Limit (CA)	1.25
MIR Value	1.03
Removal (How To)	Remove with paint stripper or other solvent.