

SAFETY DATA SHEET



BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

SECTION 1. IDENTIFICATION

Product name : BESTOLIFE STORAGE COMPOUND
SDS-Identcode : 437G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Telefax : 214-631-3047
Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887
(24-hours/7 days)
E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmospheres.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 50 - < 70
Calcium carbonate	471-34-1	>= 10 - < 20
Limestone	1317-65-3	>= 10 - < 20
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 5 - < 10
Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	57855-77-3	>= 5 - < 10
12-Hydroxy lithium stearate	7620-77-1	>= 5 - < 10
Titanium dioxide	13463-67-7	>= 1 - < 5

Actual concentration is withheld as a trade secret

SAFETY DATA SHEET



BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
Calcium carbonate	471-34-1	ST (Mist)	10 mg/m ³	NIOSH REL
		TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Limestone	1317-65-3	TWA (total dust)	15 mg/m ³	OSHA Z-1

SAFETY DATA SHEET



BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
 Date of first issue: 05/18/2015

		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
12-Hydroxy lithium stearate	7620-77-1	TWA (Inhalable fraction)	10 mg/m ³	ACGIH
		TWA (Respirable fraction)	3 mg/m ³	ACGIH
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Titanium dioxide

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous air chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Eye protection	:	breaks and at the end of workday. Wear the following personal protective equipment: Safety glasses
Skin and body protection	:	Skin should be washed after contact.
Hygiene measures	:	Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Viscous semi-solid
Color	:	off-white
Odor	:	Petroleum
Odor Threshold	:	No data available
pH	:	Not applicable (not an aqueous solution)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	1.0
Density	:	No data available
Solubility(ies)	:	
Water solubility	:	negligible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Flow time	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
 Ingestion
 Eye contact

Acute toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

Calcium carbonate:

Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral tox-
---------------------	---	---

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

icity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity

Limestone:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 420
 Assessment: The substance or mixture has no acute oral toxicity
 Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: The substance or mixture has no acute dermal toxicity

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg
 Remarks: Based on data from similar materials

BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Calcium carbonate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Limestone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Species : Rabbit
Result : No skin irritation

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Calcium carbonate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Limestone:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Species : Rabbit
Result : No eye irritation

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rabbit
Result : No eye irritation

BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Calcium carbonate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Limestone:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Result : negative

12-Hydroxy lithium stearate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Titanium dioxide:

Test Type : Local lymph node assay (LLNA)
 Routes of exposure : Skin contact
 Species : Mouse
 Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
 cytogenetic assay)
 Species: Mouse
 Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Calcium carbonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative

Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative
 Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative
 Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative
 Remarks: Based on data from similar materials

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Distillates (petroleum), hydrotreated light naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative

Distillates (petroleum), hydrotreated light naphthenic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Result : negative

Titanium dioxide:

Species : Rat

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Application Route : inhalation (dust/mist/fume)
 Exposure time : 2 Years
 Method : OECD Test Guideline 453
 Result : positive
 Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

IARC Group 2B: Possibly carcinogenic to humans
 Titanium dioxide 13463-67-7

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:**Calcium carbonate:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 414
 Result: negative

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

Distillates (petroleum), hydrotreated light naphthenic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:**12-Hydroxy lithium stearate:**

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rat
NOAEL : > 0.98 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Remarks : Based on data from similar materials

Calcium carbonate:

Species : Rat
NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422

Limestone:

Species : Rat
NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Distillates (petroleum), hydrotreated light naphthenic:

Species	: Rabbit
NOAEL	: 1,000 mg/kg
Application Route	: Skin contact
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 410

12-Hydroxy lithium stearate:

Species	: Rat
NOAEL	: > 88 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Titanium dioxide:

Species	: Rat
NOAEL	: 24,000 mg/kg
Application Route	: Ingestion
Exposure time	: 28 Days
Species	: Rat
NOAEL	: 10 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 y

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d Remarks: Based on data from similar materials

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Toxicity to microorganisms : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Remarks: Based on data from similar materials

Calcium carbonate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): 50 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC: 1,000 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

EC50: > 1,000 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

Limestone:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: No toxicity at the limit of solubility.

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d

Toxicity to microorganisms : NOEC (Photobacterium phosphoreum): > 2.17 mg/l
 Exposure time: 4 d

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10: 110 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Titanium dioxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
 Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

Persistence and degradability**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated light naphthenic:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 8 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 16 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B
 Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

SAFETY DATA SHEET



BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations**Pennsylvania Right To Know**

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Calcium carbonate	471-34-1
Limestone	1317-65-3
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	57855-77-3
12-Hydroxy lithium stearate	7620-77-1
Titanium dioxide	13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
--	------------

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Calcium carbonate	471-34-1
Limestone	1317-65-3
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Titanium dioxide	13463-67-7

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

AICS : All ingredients listed or exempt.


BESTOLIFE STORAGE COMPOUND

Version 8.1 Revision Date: 10/01/2018 SDS Number: 117366-00015 Date of last issue: 07/19/2018
Date of first issue: 05/18/2015

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EC_x - Concentration associated with x% response; EHS - Extremely Hazardous Substance; EL_x - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErC_x - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC₅₀ - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC₅₀ - Lethal Concentration to 50 % of a test population; LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of

SAFETY DATA SHEET



BESTOLIFE STORAGE COMPOUND

Version	Revision Date:	SDS Number:	Date of last issue: 07/19/2018
8.1	10/01/2018	117366-00015	Date of first issue: 05/18/2015

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/01/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8