



2-26® Multi-Purpose Precision Lubricant, 55 Gal No. 02011 | Item# 1003170

Product Description	Plastic safe lubricant, penetrant and corrosion inhibitor that helps prevent electrical malfunctions caused by water penetration, humidity, condensation or corrosion. Restores resistance values and helps stop current leakage.
Applications	Connectors, relays, circuit breakers, transformers, switchgear, motors, generators, controls, instruments, communication assemblies, electronics, alarm systems, starters, tubing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks.
Unit Package Description	55 Gallon Drum
Brand	CRC
Generic Description 1	Multi-Purpose Precision Lubricant Plastic Safe
Net Fill	55 Gal
UPC Code	078254020112
Unit Dimensions	35H x 24.5W x 24.5D in
Units Per Case	1
Case Dimensions	35H x 24.5W x 24.5D in
Cases Per Pallet	4
Case Weight	430 lbs
Appearance	Amber Liquid
Base Type	Petroleum Distillate
Flash point (F)	200°F
Flash point (C)	93°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.82
Plastic Safe	Yes
Film Type	Thin, Non-Drying
Film Thickness	0.025 to 0.075 Mil
Evaporation Rate	Slow
Dielectric Strength	51,300 Volts

Last revised: 7/30/2019
Page 1 of 2





Working Temp (F)	Max 250°F
Working Temp (C)	Max 121.1°C
Propellant	None
NSF Category Code	H2
NSF Number	017223
Military Specification Number	Not Determined
Federal Specification Number	V-V-P-216
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with Petroleum Distillates.

Last revised: 7/30/2019
Page 2 of 2