



Diesel Cold Flow™ Anti-Gel with Lubricity, 30 Fl Oz
 No. 05632 | Item# 1003834 | Case# 1003833

Product Description	A highly concentrated formula that inhibits gelling & improves flowability of diesel fuel in cold weather. Lowers the pour point by as much as 40 F. when used in the proper ratios.
Applications	For use in diesel engines.
Unit Package Description	1 Quart Can
Generic Description 1	Premium Anti Gel with Lubricity
Brand	CRC
Net Fill	30 Fl Oz
UPC Code	078254056326
Unit Dimensions	9.5H x 4.5W x 2.6D in
Units Per Case	12
Case Dimensions	16.3H x 9W x 9.4D in
Cases Per Pallet	50
Case Weight	23 lbs
I 2 of 5 Code	30078254056327
Appearance	Light Amber Liquid
Flash point (F)	93.2°F
Flash point (C)	34°C
Flammability Class - CPSC	Flammable
Spec Gravity Concentrate	0.88
Plastic Safe	No
DOT Proper Shipping Name	Flammable Liquids, N.O.S. (Xylene, Petroleum Naphtha), Limited Quantity
VOC % (Consumer Product def)	94.6
VOC g/L (Consumer Product def)	829
VOC lbs/gal (Consumer Prod def)	6.92

Last revised: 1/8/2020
 Page 1 of 2





VOC Category
 Removal (How To)
 Treatment Ratio

Not Regulated
 Remove with Petroleum Distillates.
 Preventative Maintenance: 1 Qt treats 500 Gal, Pre-existing Condition: 1 Qt treats 125 Gal