



Copper Coat® Gasket Compound, 4 Fl Oz
 No. 401504 | Item# 1006075 | Case# 1006074

Product Description	High temperature, high quality gasket sealer. Prevents compression loss on paper, cork and premium gaskets. Dauber built into the lid for easy application and storage.
Applications	Automatic transmissions, cover plates, diesel heads, high compression engines, hi-speed turbine superchargers, hydraulic pumps
Unit Package Description	4 ounce Brush Top Bottle
Brand	K&W
Generic Description 1	Gasket Compound
Net Fill	4 Fl Oz
UPC Code	078372015045
Unit Dimensions	2.75H x 2.5W x 2.5D in
Units Per Case	12
Case Dimensions	3.7H x 6.8W x 8D in
Cases Per Pallet	280
Case Weight	5 lbs
I 2 of 5 Code	10078372015042
Appearance	Viscous Copper Liquid
Flash point (F)	30°F
Flash point (C)	-1.1°C
Flammability Class - CPSC	Flammable
Spec Gravity Concentrate	0.76
Plastic Safe	Yes
Evaporation Rate	Moderate
Dielectric Strength	Not Determined
Working Temp (F)	-80 to 400°F
Working Temp (C)	-62.2 to 204.4°C
Propellant	None
DOT Proper Shipping Name	Flammable Liquids, N.O.S. (Heptane, Cyclohexane), Limited Quantity (Marine Pollutant)

Last revised: 10/8/2019
 Page 1 of 2





VOC % (Consumer Product def)	74.2
VOC g/L (Consumer Product def)	549
VOC lbs/gal (Consumer Prod def)	4.57
VOC Category	Not Regulated
Removal (How To)	Gasket remover