



**Food Grade Gear Oil SAE 85W-140, 55 Gal**  
 No. 04251 | Item# 1003558

|                           |   |
|---------------------------|---|
| Product Description       | Food grade gear lubricant that is formulated with USP grade white oils. This NSF H1 Registered food grade gear lubricant is engineered to provide superior lubrication protection where food contact may occur. |
| Applications              | Great for use in all types of food processing facilities. Gear sets, bearings, pumps, and chain applications.   |
| Unit Package Description  | 55 Gallon Drum  |
| Brand                     | CRC   |
| Generic Description 1     | Gear Oil  |
| Net Fill                  | 55 Gal  |
| UPC Code                  | 078254042510  |
| Unit Dimensions           | 34.5H x 23W x 23D in  |
| Units Per Case            | 1   |
| Case Dimensions           | 34.5H x 23W x 23D in  |
| Cases Per Pallet          | 4   |
| Case Weight               | 447 lbs   |
| Appearance                | Clear Liquid  |
| Flash point (F)           | 464°F   |
| Flash point (C)           | 240°C   |
| Flammability Class - CPSC | Combustible   |
| Spec Gravity Concentrate  | 0.88  |
| Plastic Safe              | Safe on Most Plastics (Test small area)   |
| SAE Grade                 | 85W-140   |
| ISO Viscosity Grade       | 320   |
| Working Temp (F)          | 15 to 375°F   |
| Working Temp (C)          | -9.4 to 190.6°C   |
| NSF Category Code         | H1  |
| NSF Number                | 144413  |
| DOT Proper Shipping Name  | Not Regulated   |

Last revised: 12/6/2019  
 Page 1 of 2





|                                 |                                    |
|---------------------------------|------------------------------------|
| VOC % (Consumer Product def)    | 0                                  |
| VOC g/L (Consumer Product def)  | 0                                  |
| VOC lbs/gal (Consumer Prod def) | 0                                  |
| VOC Category                    | Not Regulated                      |
| Removal (How To)                | Remove with Petroleum Distillates. |