



Food Grade Hydraulic Oil ISO 32, 5 Gal
 No. 04220 | Item# 1003539

Product Description	Food grade hydraulic fluid that is formulated with USP grade white oils. This NSF H1 registered food grade hydraulic fluid is engineered to meet the demanding requirements of severe hydraulic systems using high pressure and high output pumps.
Applications	Great for use in all types of food processing facilities. Hydraulic Systems, vacuum pumps, canning, bearings, valves, circulating oil.
Unit Package Description	5 Gallon Pail
Brand	CRC
Generic Description 1	Hydraulic Oil
Net Fill	5 Gal
UPC Code	078254042206
Unit Dimensions	15H x 12W x 12D in
Units Per Case	1
Case Dimensions	15H x 12W x 12D in
Cases Per Pallet	36
Case Weight	39 lbs
Appearance	Clear Liquid
Flash point (F)	420°F
Flash point (C)	216°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.86
Plastic Safe	Yes
Evaporation Rate	1.4
ISO Viscosity Grade	32
SAE Grade	10W
Working Temp (F)	-10 to 325°F
Working Temp (C)	-23.3 to 162.8°C
NSF Category Code	H1

Last revised: 12/6/2019
 Page 1 of 2





NSF Number	145591
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated
Removal (How To)	Remove with degreasers.