



## Food Grade Synthetic Gear Oil ISO 220, 5 Gal No. 04232 | Item# 1003549

Product Description	A fully synthetic NSF H1 Registered food grade gear oil that is formulated from premium polyalphaolefins (PAO) base fluids. It is engineered to provide superior lubrication protection and includes an additive to improve gasket and seal characteristics.
Applications	Great for use in all types of food processing facilities. Gear Sets, bearings, worm gears, chains, & circulating oil
Unit Package Description	5 Gallon Pail
Brand	CRC
Generic Description 1	Synthetic Gear Oil
Net Fill	5 Gal
UPC Code	078254042329
Unit Dimensions	15H x 12W x 12D in
Units Per Case	1
Case Dimensions	15H x 12W x 12D in
Cases Per Pallet	36
Case Weight	38 lbs
Appearance	Clear Liquid
Flash point (F)	504°F
Flash point (C)	262°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.85
Plastic Safe	Safe on Most Plastics (Test small area)
SAE Grade	50
ISO Viscosity Grade	220
Working Temp (F)	-36 to 450°F
Working Temp (C)	-37.8 to 232.2°C
NSF Category Code	H1
NSF Number	144422
DOT Proper Shipping Name	Not Regulated

Last revised: 12/6/2019  
Page 1 of 2





VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated
Removal (How To)	Remove with Petroleum Distillates.

Last revised: 12/6/2019  
Page 2 of 2