



Food Grade Synthetic Hydraulic Oil ISO 32, 5 Gal No. 04547 | Item# 1003574

Product Description	NSF H1 Fully synthetic fluid blended from premium polyalphaolefin (PAO) base oils with superior additives that meet the requirements for demanding industrial hydraulic systems within the food industry.
Applications	Great for use in all types of food processing facilities. Hydraulic Systems, vacuum pumps, canning, bearings, valves, circulating oil.
Unit Package Description	5 Gallon Pail
Brand	CRC
Generic Description 1	Hydraulic Oil
Net Fill	5 Gal
UPC Code	078254045474
Unit Dimensions	15H x 12W x 12D in
Units Per Case	1
Case Dimensions	15H x 12W x 12D in
Cases Per Pallet	24
Case Weight	35 lbs
Appearance	Clear and Bright Liquid
Flash point (F)	465°F
Flash point (C)	241°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.82
Plastic Safe	Safe on Most Plastics (Test small area)
Evaporation Rate	Not Determined
ISO Viscosity Grade	32
SAE Grade	10
Working Temp (F)	-50 to 450°F
Working Temp (C)	-45.6 to 232.2°C
NSF Category Code	H1
NSF Number	151367

Last revised: 12/6/2019
Page 1 of 2





DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated