



Food Grade Synthetic Hydraulic Oil ISO 46, 55 Gal No. 04213 | Item# 1003534

Product Description	Fully synthetic fluid blended from premium polyalphaolefin (PAO) base oils with superior additives that meet the requirements for demanding industrial hydraulic systems within the food industry.
Applications	Great for use in all types of food processing facilities. Hydraulic Systems, vacuum pumps, canning, bearings, valves, circulating oil.
Unit Package Description	55 Gallon Drum
Brand	CRC
Generic Description 1	Hydraulic Oil
Net Fill	55 Gal
UPC Code	078254042138
Unit Dimensions	34.5H x 23W x 23D in
Units Per Case	1
Case Dimensions	34.5H x 23W x 23D in
Cases Per Pallet	4
Case Weight	425 lbs
Appearance	Clear Liquid
Flash point (F)	500°F
Flash point (C)	260°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.83
Plastic Safe	Safe on Most Plastics (Test small area)
Evaporation Rate	Slow
ISO Viscosity Grade	46
SAE Grade	20
Working Temp (F)	-50 to 450°F
Working Temp (C)	-45.6 to 232.2°C
NSF Category Code	H1
NSF Number	144419

Last revised: 12/6/2019
Page 1 of 2





DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated
Removal (How To)	Remove with degreasers.