



Hydraulic & Jack Oil, 5 Gal

No. SL2555 | Item# 1007842

Product Description	A medium weight hydraulic oil blended of a high quality paraffinic base oil with anti-rust, anti-oxidation, anti-foam, anti-wear, and seal swell additives. It is a 20W, non-detergent oil.
Applications	Hydraulic systems and fluid drive units. May be added to existing fluids. Not for use in hydraulic brakes.
Unit Package Description	5 Gallon Pail
Brand	Sta-Lube
Generic Description 1	Hydraulic & Jack Oil
Net Fill	5 Gal
UPC Code	072213255508
Unit Dimensions	14.5H x 12W x 12D in
Units Per Case	1
Case Dimensions	14.5H x 12W x 12D in
Cases Per Pallet	36
Case Weight	45 lbs
Appearance	Amber Viscous Liquid
Flash point (F)	380°F
Flash point (C)	193°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.87 to 0.89
Plastic Safe	Yes
Evaporation Rate	Slow
ISO Viscosity Grade	46 to 68
SAE Grade	20
Working Temp (F)	0 to 150°F
Working Temp (C)	-17.78 to 65.56°C
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0

Last revised: 3/7/2019
Page 1 of 2





VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated

Last revised: 3/7/2019
Page 2 of 2