



Safety Anti-Slip Paint, Transparent, 12 Wt Oz
 No. 18024 | Item# 1005192 | Case# 1005191

Product Description	Anti-Slip Coating which produces a slip resistant coating which is resistant to oil, gas, and most chemicals. Use as a finish coat and recoat every 2-4 months based on traffic.
Color	Clear
Applications	Interior and exterior use on wood, metal, concrete, asphalt, railings, stairs, tools, boat docks, ramps etc.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Slip Resistant Coating
Net Fill	12 Wt Oz
UPC Code	078254180243
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	6
Case Dimensions	8.25H x 5.75W x 8.25D in
Cases Per Pallet	152
Case Weight	6 lbs
I 2 of 5 Code	30078254180244
Appearance	Clear Liquid
Flash point (F)	< -2°F
Flash point (C)	< 18.9°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.77 to 0.85
Plastic Safe	No
Evaporation Rate	Fast
Dry Time - Fully Dry	24 Hours
Dry Time - Tack Free	10 Minutes
Recoat	30 Minutes
Coverage	~7 Sq Ft

Last revised: 1/8/2020
 Page 1 of 2





Working Temp (F)	50 to 90°F
Working Temp (C)	10 to 32°C
Propellant	Hydrocarbon
Aerosol Flammability Level	III
Military Specification Number	Not Determined
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	45.5
VOC g/L (Consumer Product def)	535
VOC lbs/gal (Consumer Prod def)	4.46
VOC Category	Aerosol Coating: Slip-Resistant Coating
MIR Limit (EPA)	2.45
MIR Limit (CA)	2.1
MIR Value	1.47
Removal (How To)	Remove: WET paint with mineral spirits or turpentine, DRY paint with lacquer thinner/stripper.